

WELCOME TO USHA ENTERPRISES



U - UNDERSTANDING

S - **SINCESARLY**

H - HIGHER THINKING

A - ACCURACY

VISION & MISSION

TO ACHIEVE SATISFACTION OF COSTUMER BY,

- ACHIEVING ON TIME DELIVERY
- MINIMIZING NCR
- INCREASING PRODUCTIVITY
- STREAM LINE COMMUNICATION WITH COSTUMER

TO ACHIEVE THESE GOAL,

- WE INTERACT WITH COSTUMER TO UNDERSTAND THE PRODUCT & QUALITY REQUIREMENTS OF COMPONENT.
- WE ARRANGE TRAINING PROGRAM FOR SHOP FLOOR WORKERS.
- WE ARRANGE TRAINING PROGRAM FOR MIDDLE MANAGEMENT.
- WE ARE BUILDING A DEDICATED TRAINED TEAM OF MIDDLE MANAGEMENT.
- INSTALLED NEW GENERATION MACHINE TOOLS.
- ADOPTED NEW MACHINING PROCESSES .
- INTRODUCED HIGH QUALITY , PRECISION & LATEST TOOLINGS .
- INSTALLED HIGH PRECISION & LATEST INSPECTION TOOLS.
- IMPLICATED PROCESS CONTROL & CONSTANTLY REVIEWING THE PROCESS
- INCREASED USE OF SOFTWARE FOR MACHINING PROCESS SUCH AS FUTURE CAM IS IMPLICATED.



TOTAL AREA : 28000 SQFT.

SHOP AREA : 22000 SQFT.

OFFICE BLOCK: 1480 SQFT.

Total no. machines: 7 CNC machines & 12 conventional machines



Skilled Workers: 21

Unskilled Workers: 06

• Engineers: 11

Administration Staff: 07

TOS WHN 13.8 CNC HBM

HEIDENHAIN TNC 426 CONTROLLER



MACHINE DETAILS:

X: 3500 MM Y: 2000 MM Z: 800 MM

TABLE SIZE: 2200 X 1800 MM. SPINDLE DIA.: 130 MM



MICROCUT BUFFALO MAKE CNC CONTROLLED MACHINE 5 AXIS MACHINING CENTER



X - 2000MM, Y - 1600MM, W - 500 MM, Z - 2500MM SPINDLE DIA.- 110MM, CONTROLLER 18 IMB, SIMULTANEOUS 4 AXIS 28 ATC



CNC VTL MACHINE WITH C AXIS (LIVE SPINDLE) TABLE DIA.: Ø1200 MM., MAX DIA. OF JOB: Ø1600 MM

MAX HEIGHT OF JOB: 1600 MM



CNC VTL MACHINE



TABLE DIA.: 1600 MM

MAX. DIA. JOB: 2250 MM

MAX HEIGHT OF JOB: 1400 MM



CNC TURNING LATHE MACHINE WITH MILLING ATTACHMENT



CNC LATHE MACHINE



CMM

X: 900 MM, Y: 1500 MM, Z: 800 MM

LEAST COUNT - 0.1MICRON



SPERONI TOOL PRESETTING & MEASURING SYSTEM MAGIS 600



- Axis Travel:
- o Diameter X = 400mm (-50 / +350)
- Height Z = 600 mm
- EDGE 2.0 Control Software
- Thermal Alphanumeric Label Printer
- Automatic Mechanical Clamping System - ISO 50
- Automatic (CNC) Spindle AxisAutofocus

SEDIN RUSSIAN MAKE VTL

MAX DIA. OF JOB – Ø2500 MM MAX HEIGHT OF JOB – 1600 MM WITH DEGREE TURNING FACILITY UP TO 45°



HORIZONTAL BORING MACHINE

WMW MAKE - SPINDLE 100 MM DIA. X TRAVEL 2000MM , Y TRAVEL 1500MM



WMW HBM MACHINE - SPINDLE DIA. Ø125 TABLE TYPE - 2000 X 2000 MM



WMW HBM MACHINE - SPINDLE DIA.

Ø100

TABLE TYPE - 1500 X 1600 MM



SEDIN RUSSIAN MAKE VTL

MAX DIA. OF JOB – Ø1200 MM MAX HEIGHT OF JOB – 1000 MM



KOLB RADIAL DRILLING MACHINE

MAX STEEL CAP. -75 MM , SWING OF ARM -3300 MM , MAXIMUM HEIGHT 2700 MM





RADIAL DRILING MACHINE



UPCOMING EXPANSION

- We are in process of buying 50,000 SQFT. Of land with 15,000 SQFT of built in factory shed.
- We are expecting to complete the acquisition by April.
- We have recently purchased Double column VMC machine which will enhance our production rate of screen plate.
- In that set up like for centrifugal pumps we are planning to have testing bed for CM-21 pump ready for all times.

DUPLEX ROTOR FOR VOITH



PUMP IMPELLER & VOITH CM-21 PUMP WITH PERFORMANCE TRIAL





CM-21 ROTOR & F2TS ROTOR






SCREEN PLATE





SL 25/25 PUMP WITH 14000 LPM


























24" GATE VALVE COMPLETE MACHINED & SEAT WELDED LAPPED TESTED FOR KSB PUMPS LTD. CHINA







PRODUCT OVERVIEW USHA ENTERPRISES



8 x 15 DMX hydro testing @ 310 bar pressure



PRODUCT OVERVIEW USHA ENTERPRISES





PRODUCT OVERVIEW USHA ENTERPRISES



8 x 15 DMX hydro testing @ 310 bar pressure

THANK YOU...

